












FB_056_01_INSTRUCTION

NOTE FOR LONGER STORAGE TIMES



SPECIAL NOTES ON THE STORAGE
OF WENDT COMPONENTS
REGARDING DURABILITY AND STORAGE CONDITIONS,
PLEASE REFER TO THE PRODUCT INFORMATION FOR THE FOLLOWING PRODUCTS.

Please check for completeness and damage on delivery.

1. Sealing compound		2. Sealing tape		3. Density profile	
Air humidity: 30%-50% Storage temperature: 15°C-20°C, store frost-proof Storage at more than 25°C reduces the shelf life! Observe the expiry date on the packaging!		Humidity below 65% According to the manufacturer, storage temperature at 20°C. Protect from direct sunlight. Store at room temperature and frost-proof. Observe the expiry date on the packaging!		Air humidity below 65% Storage should be cool, dry and dust-free. Protect from direct sunlight. The storage temperature should be 15°C and shall not exceed 25°C. Observe the expiry date on the packaging!	
4. Glue		5. Lamp, Illuminant		6. Protective foil on sheet metal profiles, roof and wall elements	
Do not store in a closed container below +10°C or above +30°C. Observe the expiry date on the packaging!		Humidity: 60%. Protect from moisture and dew formation and Protect direct sunlight.		Protect from high temperature, frost, (5°C ≤ T Storage ≤ 45°C), moisture and direct sunlight. Note - Object and ambient temperature: ≥ 5°C ➤ Pull off foil after 6 months after readiness for shipment at the latest!	
7. Battery		8. Fan		9. Paint, hardener	
Storage time: depending on storage temperature Store batteries within the specified temperature range at low humidity.		It is recommended that regular checks be carried out to check the proper condition of the fan during storage; Please note the manufacturer's specifications and technical documentation. Rotate and log the wing wheel at regular intervals!		Storage temperature: 5°C-40°C, store in a frost-proof and dry place. Protect from direct sunlight. Please note the expiry date on the packaging!	

Important - The pictures are examples and are for display only!

We reject any warranty obligation if the aforementioned information has not been taken into account.

WENDT Noise Control GmbH
Beindersheimer Straße 79 * D-67227 Frankenthal
Telefon (+49) 06233 7704 0 * Fax (+49) 06233 7704 70
E-Mail – Adresse: info@wendt-noise-control.de
Deutschland

